

### DIN1837 HSS Slitting Saws

- Manufacturing process: fully ground
- Material: HSS, HSS-Co
- Finish: bright, TiN
- Diameter: 40-200mm



D	Thickness	H	Teeth
40	0.3	10	100
40	0.4	10	100
40	0.5	10	80
40	0.6	10	80
40	0.8	10	80
40	1	10	64
40	1.2	10	64
40	1.6	10	64
40	2	10	48
50	0.4	13	100
50	0.5	13	100
50	0.6	13	100
50	0.8	13	80
50	1	13	80
50	1.2	13	80
50	1.6	13	64
50	2	13	64
63	0.4	16	128
63	0.5	16	128
63	0.6	16	100
63	0.8	16	100
63	1	16	100
63	1.2	16	80
63	1.6	16	80
63	2	16	80
80	0.4	22	128
80	0.5	22	128
80	0.6	22	128

D	Thickness	H	Teeth
80	22	0.8	128
80	22	1	100
80	22	1.2	100
80	22	1.6	100
80	22	2	80
100	22	0.5	160
100	22	0.6	160
100	22	0.8	128
100	22	1	128
100	22	1.2	128
100	22	1.6	100
100	22	2	100
125	22	0.6	160
125	22	0.8	160
125	22	1	160
125	22	1.2	128
125	22	1.6	128
125	22	2	128
125	22	2.5	100
125	22	3	100
160	32	1	160
160	32	1.2	160
160	32	1.6	160
160	32	2	128
160	32	2.5	128
160	32	3	128
200	32	2	160